

## PRODUCT SPECIFICATIONS



## PET PLATINUM

Offering superior durability in high foot traffic areas is what sets this artificial grass variety apart from the rest of the pack. Ideal turf for a multitude of applications where durability and reliability matter.

		Unmatched Lifetime Warranty	
SKU	ST343 PETS	EnviroLoc+ <sup>™</sup> Plant-Based Backing	
Grass Zone Yarn/Color	PE / Field Green / Apple		
Grass Zone Denier	10,800 / 6	Deluster + UV Protection	
Thatch Zone Yarn/Color	PE / Field Green / Beige	ASTM E108 Class A Fire Rating	
Thatch Zone Denier	5,000 / 8		
Grass Zone Yarn Shape	Omega	SUPER YARN <sup>™</sup> TECHNOLOGY	
Finished Pile Height	1 1/2"		
Finished Pile Weight	80 oz.	Sanitized®DualChill™StatBlock™AntimicrobialIR ReflectiveAnti-Static	
Backing	15 / 18 PP 2-Part / 22oz. EnviroLoc+™		
Tuft Gauge	3/8"		
Total Weight	108 oz.	Artificial Grass Fiber	
Tuft Bind	> 8 lbs.	Compacted Aggregate Base	
Permeability	> 1,200 inches per / SY	Geotextile Weed Barrier	
Features	Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, Deluster, UV Stabilizers	C Learn more at CADdetails.com Not to scale. For illustration only. RECOMMENDED USES	
Test Data	ASTM E108 Class A Fire Rating, F1292, F1551, F1951, IPEMA Certified	LANDSCAPE — PETS — PLAY — ROOFTC	







For ordering and questions, contact SYNLawn at 866-796-5296 or visit SYNLawn.com



## PET PLATINUM

f y in C G 0

Primary Yarn Polymer	Polyethylene			
Yarn Cross Section	Omega	Primary Backing	15/18 PP 2-Part	
Standard Color	Field Green / Apple	Coating Type	22 oz. EnviroLoc+	
Fabric Construction	Tufted	PE Yarn Denier / Ends	10,800 / 6	
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier / Ends	5,000 / 8	
Secondary Yarn Color	Field Green / Beige	Warranty Period	Limited Lifetime	

Finish Fabric	English System		ASTM Test
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	80	oz/yd²	D-5848
Total Fabric Weight	108	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	> 1,200	in/hr	D-1551
Fabric Width	15	ft	