

Grass Zone Yarn/Color

Grass Zone Denier

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile Weight

Backing

Tuft Gauge

Total Weight

Tuft Bind

Permeability

Features

Test Data

SR200

Nylon / Field Green

4,200/8

Nylon / Turf Green

4,200/8

Diamond Mono

1 1/8"

60 oz.

13 / 18 PP 2-Part / 22oz. EnviroLoc+™

3/8"

88 oz.

> 8 lbs.

> 500 inches per / SY

EnviroLoc+™, HeatBlock™, **UV Stabilizers**

ASTM E108 Class A Fire Rating, E648, F1292, F1951, IPEMA Certified

ROOFDECK PLATINUM

The ultimate artificial roof, deck, and patio grass for performance and safety. Nylon fibers provide a high melt, resistance against window reflectivity, and the highestrated safety rating in the industry. ASTM Certified E108 Class A Fire-Rated, ASTM E648, F1292, F1951.



Unmatched Lifetime Warranty



EnviroLoc+™ Plant-Based Backing



Deluster + UV Protection



ASTM E108 Class A Fire Rating



RECOMMENDED USES





















Primary Yarn Polymer	Nylon
Yarn Cross Section	Diamond Mono
Standard Color	Field Green
Fabric Construction	Tufted
Second Yarn Polymer Thatch	Nylon
Secondary Yarn Color	Turf Green

Primary Backing	13/18 PP 2-Part	
Coating Type	22 oz. EnviroLoc+	
PE Yarn Denier / Ends	4,200 / 8	
Texturized Thatch Denier / Ends	4,200 / 8	
Warranty Period	Limited Lifetime	

Finish Fabric	English	System	ASTM Test
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/8	inches	D-5823
Face Weight	60	oz/yd²	D-5848
Total Fabric Weight	88	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	8,400	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	512.19	in/hr	D-1551
Fabric Width	15	ft	-







