

SKU	RANGE
Grass Zone Yarn/Color	PE / Field Green / Lime / White
Grass Zone Denier	10,000 / 1
Thatch Zone Yarn/Color	-
Thatch Zone Denier	-
Grass Zone Yarn Shape	Slit Film
Finished Pile Height	1 1/4"
Finished Pile Weight	41 oz.
Backing	13PP/18PET 2pt/22oz EnviroLoc+™
Tuft Gauge	3/8"
Total Weight	69 oz.
Tuft Bind	> 8 lbs.
Permeability	> 400 inches p/hr
Features	Deluster UV Stabilizers
Test Data	-

## **SYNRANGE PRO**

Ideal turf product for large indoor or outdoor applications such as golf facilities and driving ranges. Highly durable with a low face weight and a natural aesthetic are among the many benefits when choosing this golf grass variety.



## **3 COLORS AVAILABLE**

FIELD GREEN | LIME | WHITE ASK ABOUT CUSTOM COLORS



10 YEAR WARRANTY



**UV PROTECTION** 



DELUSTER



INSTALLATION SYSTEM









INSTALLER







Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Slit Film	Primary Backing	13PP/18PET 2pt
Standard Color	PE Field Green/Lime/White	Coating Type	22 oz. EnviroLoc+
Fabric Construction	Tufted	PE Yarn Denier / Ends	10,000 / 1
Second Yarn Polymer Thatch		Texturized Thatch Denier / Ends	-
Secondary Yarn Color		Warranty Period	10 Years

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/4"	inches	D-5823
Face Weight	41	oz/yd²	D-5848
Total Fabric Weight	69	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	10,000	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Guage	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 400	in/hr	D-1551
Fabric Width	15	ft	-

