



SKU	S547B
Grass Zone Yarn/Color	PE / Sport Green/Apple/Olive
Grass Zone Denier	9,900/9
Thatch Zone Yarn/Color	PE / Field Green/Beige
Thatch Zone Denier	5,000/8
Grass Zone Yarn Shape	Biomimetic™ U
Finished Pile Height	1 3/8"
Finished Pile / Total Weight	50 oz. / 78 oz.
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Tuft Bind	> 8 lbs.
Permeability	> 800 inches p/hr
Features	Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, Deluster, UV Stabilizers, Biomimetic™
Test Data	EN 12616, CAL1350, ASTM D2859, ASTM D7138, ASTM E108, ASTM E648, ASTM

## **SYNAUGUSTINE 547**

SYNAugustine 547, a USDA Certified Bio-Based turf, combines Super Yarn™ Technology with renewable sugarcane for durability and eco-friendliness. With soft, vibrant multi-tone blades, it's a stunning, sustainable, and cost-effective landscaping solution.



## **SUPER YARN™ TECHNOLOGY**

**SANITIZED**® ANTIMICROBIAL **DUALCHILL™** IR REFLECTIVE

STATBLOCK™ ANTI-STATIC



LIMITED LIFETIME WARRANTY



OPTIMAL DRAINAGE > 800" P/HR



BIOMIMETIC™ TECHNOLOGY



MADE WITH SOYBEANS + SUGARCANE

ASK ABOUT OUR...
USDA CERTIFIED
ORGANIC INFILL
SYSTEM



SYNAugustine 547 is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased content.













F1015, ASTM F1292, ASTM F1551, ASTM

F2765, EN-71, RCRA 8 TCLP









## **SYNAUGUSTINE 547**



## Official Synthetic Surface

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Biomimetic™ U	Primary Backing	13PP/18PET 2pt
Standard Color	Sport Green/Apple/Olive	Coating Type	22 oz. EnviroLoc+
Fabric Construction	Tufted	PE Yarn Denier / Ends	9,900/9
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier / Ends	5,000/8
Secondary Yarn Color	Field Green/Beige	Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 3/8	inches	D-5823
Face Weight	50	oz/yd²	D-5848
Total Fabric Weight	78	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	14,900	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	>800	in/hr	EN 12616
Fabric Width	15	ft	-

