

SKU	BL545	
Grass Zone Yarn/Color	PE / Field Green/Olive/Tan	
Grass Zone Denier	10,500/7	
Thatch Zone Yarn/Color	PE / Field Green/Beige	
Thatch Zone Denier	5,000/8	
Grass Zone Yarn Shape	S+W+Diamond	
Finished Pile Height	1 1/2"	
Finished Pile / Total Weight	55 oz./84 oz.	
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™	
Tuft Gauge	3/8"	
Tuft Bind	> 8 lbs.	
Permeability	> 400 inches p/hr	
Features	Sanitized®, EnviroLoc+™	
Test Data	EN 12616, CAL1350, ASTM D2859, ASTM E648, ASTM F1292, ASTM F1951, EN-71, RCRA 8 TCLP	

## **SYNBLUE 545**

SYNBlue 545 offers a perfect blend of realism and durability, featuring soft, multi-colored turf fibers with a natural thatch for added depth and authenticity. With antimicrobial protection and superior drainage, this low-maintenance turf ensures lasting beauty and performance, making it an ideal choice for residential or commercial landscapes.







IDEAL FOR LAWN AND LANDSCAPE APPLICATIONS





















## SYNBLUE 545



## Official Synthetic Surface

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	S+W+Diamond	Primary Backing	13PP/18 PET 2pt
Standard Color	Field Green/Olive/Tan	Coating Type	22 oz. EnviroLoc+
Fabric Construction	Tufted	PE Yarn Denier / Ends	10,500/7
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier / Ends	5,000/8
Secondary Yarn Color	Field Green/Beige	Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH SYSTEM		ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	55	oz/yd²	D-5848
Total Fabric Weight	84	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,500	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 400	in/hr	EN 12616
Fabric Width	15	ft	-





