

SKU		В

Grass Zone Yarn/Color

Grass Zone Denier

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finised Pile / Total

Weight

Backing

Tuft Gauge

Tuft Bind

Permeability

Features

Test Data

BL745

PE / Field Green/Olive/Tan

10,500/7

PE / Field Green /Beige

5,000/8

S+W+Diamond

2"

75 oz. / 104 oz.

13PP/18PET 2pt / 22oz. EnviroLoc+™

3/8"

> 8 lbs.

> 400 inches p/hr

Sanitized®, EnviroLoc+™

EN 12616, CAL1350, ASTM D2859, ASTM E648, ASTM F1292, ASTM F1951, EN-71, RCRA 8 TCLP

SYNBLUE 745

SYNBlue 745 delivers unmatched realism with soft, multi-colored turf blades that replicate natural grass. Engineered for residential and commercial landscapes, this durable, low-maintenance turf offers superior drainage, antimicrobial protection, and lasting aesthetic appeal.



LIMITED LIFETIME WARRANTY



OPTIMAL DRAINAGE >400" P/HR



SANITIZED® ANTIMICROBIAL PROTECTION



IDEAL FOR LAWN AND LANDSCAPE APPLICATIONS



















SYNBLUE 745



Official Synthetic Surface

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	S+W+Diamond	Primary Backing	13PP/18PET 2pt
Standard Color	Field Green/Olive/Tan	Coating Type	22oz. EnviroLoc+
Fabric Construction	Tufted	PE Yarn Denier/Ends	10,500/7
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier/Ends	5,000/8
Secondary Yarn Color	Field Green/Beige	Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH	ENGLISH SYSTEM	
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	2	inches	D-5823
Face Weight	75	oz/yd²	D-5848
Total Fabric Weight	104	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,500	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	>400	in/hr	EN 12616
Fabric Width	15	ft	-



