


SKU	SWN60
Grass Zone Yarn/Color	PE / Field Green / Apple / Dark Green
Grass Zone Denier	6,800 / 8
Thatch Zone Yarn/Color	PP / Olive Green / Beige
Thatch Zone Denier	3,500 / 8
Grass Zone Yarn Shape	S Shape Mono
Finished Pile Height	1 1/4"
Finished Pile/Total Weight	60 oz. / 89 oz.
Backing	SmartWeave / PCR Spray Coat
Tuft Gauge	N/A
Tuft Bind	> 12 lbs.
Permeability	> 5,500 inches p/hr
Features	Deluster, UV Stabilizers
Test Data	EN 12616, ASTM F1951, ASTM D5034-09, ASTM D1335-05

## **SYNCANINE**

Engineered for pets and heavy use, SYNCanine features SmartWeave™ Technology, delivering unmatched drainage through its innovative backing design. Combined with non-directional fibers for a natural look and enhanced durability, this turf is ideal for creating reliable, low-maintenance, and pet-friendly spaces.



SUPERIOR DRAINAGE



















## **SYNCANINE**



## Official Synthetic Surface

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	S Shape Mono		
Standard Color	Field Green / Apple / Dark Green		
Fabric Construction	Woven		
Second Yarn Polymer Thatch	Polypropylene		
Secondary Yarn Color	Olive Green / Beige		

Primary Backing	SmartWeave	
Coating Type	PCR Spray Coat	
PE Yarn Denier / Ends	6,800 / 8	
Texturized Thatch Denier / Ends	3,500/8	
Warranty Period	Limited Lifetime	

FINISH FABRIC	ENGLISH	ENGLISH SYSTEM	
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/4	inches	D-5823
Face Weight	60	oz/yd²	D-5848
Total Fabric Weight	89	oz/yd²	D-5848
Primary Backing Weight	25	oz/yd²	D-5848
Secondary Coating Weight	6-9	oz/yd²	D-5848
Tuft Bind	> 12	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	10,300	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	\-	_	-
Flammability	-	-	
Water Permeability	> 5,500	in/hr	EN 12616
Fabric Width	15	ft	-

