

## **SYNFESCUE 60**

Experience the perfect blend of realism and elegance with one of our top-selling turf styles, ideal for both residential lawns and commercial landscaping projects. Enjoy the beauty and sophistication it brings to any outdoor space.

SKU		

Grass Zone Yarn/Color

**Grass Zone Denier** 

Thatch Zone Yarn/Color

**Thatch Zone Denier** 

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile / Total Weight

Backing

Tuft Gauge

Tuft Bind

Permeability

**Features** 

Test Data

FES60

PE / Field Green/Apple

10,800/6

PE / Field Green/Beige

5,000/8

C/S

1 1/2"

60 oz./88 oz.

13PP/18PET 2pt / 22oz. EnviroLoc+™

3/8"

> 8 lbs.

> 400 inches p/hr

EnviroLoc+™, Deluster, UV Stabilizers

ASTM F1951, ASTM F1551, ASTM F1292, ASTM D2859, BS EN 13746



LIMITED LIFETIME WARRANTY



OPTIMAL DRAINAGE > 400" P/HR



HEATBLOCK TECHNOLOGY



IDEAL FOR NATURAL LAWN AESTHETICS





















## **SYNFESCUE 60**



## Official Synthetic Surface

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	C/S	Primary Backing	13PP/18PET 2pt
Standard Color	Field Green/Apple	Coating Type	22 oz. EnviroLoc+
Fabric Construction	Tufted	PE Yarn Denier / Ends	10,800/6
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier / Ends	5,000/8
Secondary Yarn Color	Field Green/Beige	Warranty Period	Limited Lifetime

FINISH FABRIC ENGLISH S		SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	60	oz/yd²	D-5848
Total Fabric Weight	88	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 400	in/hr	D-1551
Fabric Width	15	ft	-

