

SKU	F

Grass Zone Yarn/Color

**Grass Zone Denier** 

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile / Total Weight

Backing

**Tuft Gauge** 

**Tuft Bind** 

Permeability

**Features** 

**Test Data** 

## FES80

PE / Field Green / Apple

10,800 / 6

PE / Beige / Brown

5,000/8

C/S

1 3/4"

80 oz. / 108 oz.

13PP/18PET 2pt / 22oz. EnviroLoc+™

3/8"

> 8 lbs.

> 400 inches p/hr

EnviroLoc+™, Deluster, UV Stabilizers

ASTM F1292, ASTM F1951, ASTM D2859

## **SYNFESCUE 80**

An ideal solution for residential lawns and low-traffic commercial landscapes, SYNFescue 80's multicolored grass blades offer a realistic look with minimal maintenance. Designed with HeatBlock technology, this turf stays cooler underfoot while delivering superior durability.



LIMITED LIFETIME WARRANTY

























## **SYNFESCUE 80**



## Official Synthetic Surface

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	C/S	Primary Backing	13PP/18PET 2pt
Standard Color	Field Green / Apple	Coating Type	22 oz. EnviroLoc+
Fabric Construction	Tufted	PE Yarn Denier / Ends	10,800/6
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier / Ends	5,000/8
Secondary Yarn Color	Beige / Brown	Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 3/4	inches	D-5823
Face Weight	80	oz/yd²	D-5848
Total Fabric Weight	108	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 400	in/hr	D-1551
Fabric Width	15	ft	-

