

CKI	ī
21/1	J

Grass Zone Yarn/Color

Grass Zone Denier

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile / Total

Weight

Backing

Tuft Gauge

Tuft Bind

Permeability

Features

Test Data

SR246

Nylon / Sport Green/Apple/Tan

5,400/9

Nylon / Field Green/Beige

5,400/9

Diamond Mono

1 1/8"

60 oz. / 88 oz.

18/18 pic PP 2-Part/22oz. EnviroLoc+™

3/8"

> 8 lbs.

> 500 inches p/hr

EnviroLoc+™, UV Stabilizers

EN12616, ASTM C518, CAL1350, ASTM D2859, ASTM D7138, ASTM E-108, ASTM E648, EN-71

SYNRYE 246

SYNRye 246 offers a natural, earthy appearance with tan undertones that blend seamlessly into any environment. Ideal for high-traffic areas like schools and office buildings, this turf combines realistic aesthetics with top-tier performance. Featuring an ASTM CERTIFIED E108 CLASS A fire rating, HeatBlock Technology, and UV protection, it ensures safety, durability, and long-lasting beauty in even the most demanding spaces.



ASTM E108 CLASS A FIRE RATING



LIMITED LIFETIME WARRANTY



UV PROTECTED FROM REFLECTING LIGHT



FOR HIGH-TRAFFIC ROOTOPS & PLAYGROUNDS

















SYNRYE 246



Official Synthetic Surface

Primary Yarn Polymer	Nylon	
Yarn Cross Section	Diamond Mono	
Standard Color	Sport Green/Apple/Tan	
Fabric Construction	Tufted	
Second Yarn Polymer Thatch	Nylon	
Secondary Yarn Color	Field Green/Beige	

Primary Backing	18/18 pic PP 2-Part	
Coating Type	22 oz. EnviroLoc+	
PE Yarn Denier / Ends	5,400/9	
Texturized Thatch Denier / Ends	5,400/9	
Warranty Period	Limited Lifetime	

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/8	inches	D-5823
Face Weight	60	oz/yd²	D-5848
Total Fabric Weight	88	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	10,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 500	in/hr	EN 12616
Fabric Width	15	ft	-

